



## Glass Windshield for Vent Racing RZR CAGE

For RZR 1K, Turbo, Turbo S, PRO XP

(Different hardware is used depending on model)

### Hardware:

(qty)

- 4 1.75" Billet Clamps (Black)
- 4 1/4"x 2" Bolts
- 4 1/4"x 1/2" Bolts (Bottom Bolts for no tabs)
- 2 1/4"x 3/4" Bolts (Top Bolts on RZR 1k/ Turbo/ Turbo S Only)
- 4 1/4" Flat Washers
- 2 1/4" Spacer (Top Mount Spacers for RZR 1k/ Turbo/ Turbo S Only)
- 1 48" Piece of edge trim (small)
- 1 44" Edge Seal
- 2 L brackets for bottom mounts  
(optional hardware if cage has welded tabs)

**Step 1:** Install rubber edge trim on top and bottom edge for protection during install and use. (use smaller trim on top edge). Trim may need to be cut to length.

**Step 2.** Clip the billet mounts into approximate positions onto roll cage as shown in picture. Use 2" long bolts to hold clamp in place. Only tighten Bolt enough to hold clamp in place but still moveable. (if you have tabs welded to your cage you will not have lower Clamps. You will use the L brackets included.)



**Step 3.** Place windshield on cage and clamps. move clamps to line up with holes on windshield frame.

On RZR1K, Turbo, Turbo S Use .25" Spacer and 3/4" long bolts on the **TOP** mounts only, and 1/2" bolts on bottom mounts.

On RZR PRO models use 1/2" long bolts on all 4 mounts without spacers.

If using the L brackets, bolt them on with the top cage bolts.

**Step 4.** When windshield is in correct position, tighten the 2" long bolts on the clamps to lock them into position. You can leave the clamps on the roll cage if you take off the windshield to keep the same position when re-installed.

